

- Meet IMO MSC.338 (91) and IMO MSC.149 (77) regulation
- Designed for onboard fire-fighter's communication
- Ex-proof certificated
- CCS type approval



According to IMO MSC.338 (91) & SOLAS Chapter II-2, regulation 10.10.4:

### **Fire-fighter's communication**

A minimum of TWO two-way portable radiotelephone apparatus for each fire party for fire-fighter's communication shall be carried on board. Those two-way portable radiotelephone apparatus shall be of an explosion-proof type or intrinsically safe.



## SPECIFICATIONS

- Frequency range: 156.300 ~ 156.875MHz
- Channel Space: 25kHz
- Usable Channels: 19 Channels (default)
- Output Power: High 3.0W / Low 0.5W
- Communication Methods: Simplex
- Warming Up Time: Within 5 Sec
- Squelch Control: ✓
- Dual Watch: ✓
- Key Locking: ✓
- Battery Save Mode: ✓
- Beep Establishment: ✓
- Location Indication: ✓
- Operating Temperature: -20°C ~ + 60°C
- Dimension: 56 (W) × 33 (D) × 256 (H) mm
- Weight: 280g (Transceiver+Battery)
- IP Grade: IP67
- Ex code: Exib IIB T4 Gb
- Battery Capacity: 2200mAh
- Battery Voltage: 7.2V (DC)

## EQUIPMENT LIST

- **STANDARD**
  - Transceiver & Antenna 1 set
  - Rechargeable Battery Pack 1 pc
  - Battery Charger 1 pc
  - AC/DC adaptor 1 pc
  - Belt Clip 1 pc
  - Wrist Rope 1 pc
- **OPTIONS**
  - External PTT & Skull Mic/Headset 1 set



Rechargeable  
Battery Pack



Belt Clip



Battery Charger



AC/DC Adapter



Wrist Rope



Skull Mic/Headset



External PTT



## SIZE DIMENSION

